


PMF

FLAT HOLDERS, FOR FLAT TAGS, PLASTICIZED PVC



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	80 °C
Colour	Transparent
Self-extinguishing fire class according to UL 94	V0

LOGISTIC

Customs code	39269097
--------------	----------

PMF-00

Range of cable housing diameter
1.3 ÷ 2.2 mm

Range of cable cross section
0.25 ÷ 0.5 mm²

tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90000	Plasticised transparent PVC	No	No	4.8	10	0,150	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90020	Plasticised transparent PVC	No	No	4.8	15	0,226	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90040	Plasticised transparent PVC	No	No	4.8	20	0,268	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90090	Plasticised transparent PVC	No	No	4.8	40	0,580	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90070	Plasticised transparent PVC	No	No	4.8	15	0,400	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90010	Plasticised transparent PVC	No	No	4.8	12	0,186	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]

PMF-01

Range of cable housing diameter
2 ÷ 3.7 mm

Range of cable cross section
0.5 ÷ 2.5 mm²

tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90100	Plasticised transparent PVC	No	No	5	10	0,195	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90110	Plasticised transparent PVC	No	No	5	12	0,266	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90120	Plasticised transparent PVC	No	No	5	15	0,309	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90140	Plasticised transparent PVC	No	No	5	20	0,417	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90170	Plasticised transparent PVC	Yes	No	4	30	0,520			Labelling material [EC001288]
90180	Plasticised transparent PVC	No	No	5	1000	41,840	10 ÷ 25	45 ÷ 55	
90190	Plasticised transparent PVC	Yes	No	4	40	0,725			Labelling material [EC001288]

PMF-02

Range of cable housing diameter
3.4 ÷ 4.3 mm

Range of cable cross section
2.5 ÷ 4 mm²

tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90200	Plasticised transparent PVC	No	No	5.1	10	0,251	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90210	Plasticised transparent PVC	No	No	5.1	12	0,313	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90220	Plasticised transparent PVC	No	No	5.1	15	0,373	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90240	Plasticised transparent PVC	No	No	5.1	20	0,515	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90270	Plasticised transparent PVC	Yes	No	4	30	0,680			Labelling material [EC001288]

tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90290	Plasticised transparent PVC	Yes	No	4	40	0,876			Labelling material [EC001288]
PMF-03	Range of cable housing diameter 4 ÷ 6.3 mm		Range of cable cross section 4 ÷ 10 mm²						
tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90300	Plasticised transparent PVC	No	No	7.6	10	0,342	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90310	Plasticised transparent PVC	No	No	7.6	12	0,468	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90320	Plasticised transparent PVC	No	No	7.6	15	0,517	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90340	Plasticised transparent PVC	No	No	7.6	20	0,750	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90370	PVC	Yes	No	4	30	1,068			Labelling material [EC001288]
90390	PVC	Yes		4	40	1,538			Labelling material [EC001288]
PMF-04	Range of cable housing diameter 6 ÷ 10 mm		Range of cable cross section 10 ÷ 25 mm²						
tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90400	Plasticised transparent PVC	No	No	9	10	0,453	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90410	Plasticised transparent PVC	No	No	9	12	0,560	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90420	Plasticised transparent PVC	No	No	9	15	0,695	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90440	Plasticised transparent PVC	Yes	No	4	20	0,996			Labelling material [EC001288]
90470	Plasticised transparent PVC	No	No	9	30	1,434	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90490	Plasticised transparent PVC	Yes		4	40	1,504			Labelling material [EC001288]
PMF-05	Range of cable housing diameter 9 ÷ 15 mm		Range of cable cross section 25 ÷ 70 mm²						
tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90500	Plasticised transparent PVC	No	No	15.9	10	0,830	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90510	Plasticised transparent PVC	No	No	15.9	12	1,000	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90520	Plasticised transparent PVC	Yes	No	4	15	1,220			Labelling material [EC001288]
90540	Plasticised transparent PVC	No	No	15.9	20	1,760	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90570	Plasticised transparent PVC	Yes	No	4	30	2,593			Labelling material [EC001288]

tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°C]	Relative humidity of storage	ETIM Class 7
90590	Plasticised transparent PVC	No	No	15,9	40	3,450	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]

PMF-06

Range of cable housing diameter
14 ÷ 26 mm

Range of cable cross section
70 ÷ 240 mm²

tipo	Material	Silicone-free	Halogen free	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°C]	Relative humidity of storage	ETIM Class 7
90600	Plasticised transparent PVC	No	No	20,4	10	1,700	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90610	Plasticised transparent PVC	No	No	20,4	12	1,880	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90620	Plasticised transparent PVC	No	No	20,4	15	2,660	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90640	Plasticised transparent PVC	Yes	No	4	20	4,100			Labelling material [EC001288]
90670	Plasticised transparent PVC	No	No	20,4	30	5,260	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90690	Plasticised transparent PVC	No	No	20,4	40	6,622	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]