

## MG-TPM



### CERTIFICATIONS & APPROVALS


 UL (cURus)

## Features

### TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0
Sheet elements	45
Number of lines	4
Number of columns	13

### WEIGHT AND DIMENSIONS

Width	4 mm
Base of the printable area	4 mm

### CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

### MATERIAL COMPOSITION AND TREATMENTS

Silicone-free	Yes
Halogen free	Yes

### LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39206100

### COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PWC

## MG-TPM

tipo	Colour	Material	L [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
40090	White	Polycarbonate PC10300WH	10	10	0,250	1
40091	White	Polycarbonate PC10300WH	12	12	0,256	2
40040	Yellow	Polycarbonate PC10400YE	10	10	0,218	1
40041	Yellow	Polycarbonate PC10400YE	12	12	0,255	2
40092	White	Polycarbonate PC10300WH	15	15	0,302	3
40093	White	Polycarbonate PC10300WH	18	18	0,272	4
40042	Yellow	Polycarbonate PC10400YE	15	15	0,274	3
40043	Yellow	Polycarbonate PC10400YE	18	18	0,272	4



Via Serenissima, 9 - 25135  
Brescia - ITALY