

Digital clamp meter 600 V



Compliance marks



GENERAL INFORMATION

Description

Comes with LCD display and one 9 V battery.

Technical details

Display: LCD 4000 measurements.

AC power: 50/60 Hz (AAC).

TRMS.

Voltage bandwidth: AC 50/60 Hz (VAC).

Operating temperature: -10 °C to +50 °C.

Storage temperature: -30 °C to +60 °C.

Relative humidity: 90% (0 °C to 30 °C), 75% (30 °C to 40 °C), 45% (40 °C to 50 °C).

Operating altitude (m): 3000.

Storage (m): 10,000.

Overvoltage: category III 600 V.

Battery: one 9 V battery.

Automatic shut-off: after approx. 35 min.

Dimensions (mm): 229 x 80 x 49.

Weight (g): 303.

Safety: for indoor use and overvoltage category II, pollution degree 2.

Category II includes local level, appliances, portable equipment, etc. with transient overvoltages than overvoltage category III.



LOGISTIC INFORMATION

Packaging

**Carton box**

Height (cm) : 25

Length (cm) : 14

Depth (cm) : 6

Net weight (kg) : 0,303

Gross weight (kg) : 0,573



3 700882 189127

Outer package 1



x 30.00

Carton box

Height (cm) : 45

Length (cm) : 33

Depth (cm) : 52

Net weight (kg) : 17,2

Gross weight (kg) : 18,2



3 700882 195470

Outer package 2



x 180.00

Pallet

Height (cm) : 119

Length (cm) : 120

Depth (cm) : 90

Net weight (kg) : 109,2

Gross weight (kg) : 130,2



3 700882 195517