



MPN: NL883S

Product Name: 150mm White Standard With Pullcord + Auto Shutter Wall/Window Axial Fan

Brand: Newlec

Category: Domestic Fans

Product Description: The 6" (150mm) intermittent extract fan is designed for kitchens and utilities where a higher rate of extraction is required. It operates most efficiently when wall or ceiling mounted, extracting polluted air directly out of the property without the need for extra ducting.

Key Features:

- CE marked and BEAB approved.
- Extract rate: 68l/s.
- High-quality ABS moulding.
- Power consumption: 30W.
- Sound level dB(A) @ 3m: 45.
- Suitable for panel, wall, or ceiling mounting.
- Toggle action leverage to reduce operator effort.
- Automatic handle opening.

Specifications:

- Air volume, free flow (m³/h): 244.8
- Connection voltage (V): 240
- Electrical power take-up (W): 25
- Electrical connection: Terminals (EV020300)
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 225
- Width (mm): 218
- Recess diameter (mm): 150
- Power consumption (W): 25

ETIM class-9.0: Wall mounted fan (recessed mounted) (EC010930)

ETIM features:

- Air volume, free flow (m³/h): 244.8
- Connection voltage (V): 240
- Electrical power take-up (W): 25
- Electrical connection: Terminals (EV020300)
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 225
- Width (mm): 218
- Recess diameter (mm): 150
- Power consumption (W): 25
- Degree of protection (IP rating): IP44 (EV006418)
- Operation: Pull cord (EV000239)
- Humidity sensor: None (EV000494)
- Louvre/shutter: With pull cord (EV022067)
- With non-return valve: No
- Colour: White (EV000202)

Applications:

- Suitable for use in kitchens and utilities where a higher rate of extraction is required.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!