



MPN: NL880H

Product Name: Standard Humidistat And Pullcord 100mm White Wall/Window Axial Fan

Brand: Newlec

Category: Domestic Fans

Product Description: The Standard Humidistat and Pullcord 100mm White Wall/Window Axial Fan is a 4" (100mm) intermittent extract fan designed for use in bathrooms, ensuites, and toilets. It operates most efficiently when wall or ceiling mounted, extracting polluted air directly out of the property without the need for extra ducting.

Key Features:

- CE marked and BEAB approved.
 - Extract rate: 24l/s.
 - Can be wall or ceiling mounted.
 - High-quality ABS mouldings.
 - Power consumption: 16W.
 - Sound level dB(A) @ 3m: 32.
-

Specifications:

- Air volume, free flow (m³/h): 86.4
- Connection voltage (V): 240
- Electrical power take-up (W): 16
- Electrical connection: Terminals
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 154
- Width (mm): 154

ETIM class-9.0: Wall mounted fan (recessed mounted) (EC010930)

ETIM features:

- Air volume, free flow (m³/h): 86.4
- Connection voltage (V): 240
- Electrical power take-up (W): 16
- Electrical connection: Terminals (EV020300)
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 154
- Width (mm): 154
- Recess diameter (mm): 100
- Power consumption (W): 16
- Degree of protection (IP rating): IP44 (EV006418)
- Operation: Pull cord (EV000239)
- Humidity sensor: None (EV000494)
- Louvre/shutter: With pull cord (EV022067)
- With non-return valve: No
- Colour: White (EV000202)

Applications:

- Suitable for use in bathrooms, ensuites, and toilets in residential properties.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!