



MPN: NLNY25SF

Product Name: 25mm Conduit Flexible Gland Push Fit Straight IP66 PVC Black Complete With Locknut

Brand: Newlec

Category: PVC Flexible Conduit & Accessories

Product Description: The NLNY25SF is a halogen-free straight fitting designed for insertion into threaded entries and knockouts involving nylon conduits. It features a black plastic housing and is suitable for use with 25mm nominal tube diameter. The fitting is self-extinguishing and halogen-free, ensuring safety and compliance with regulations. It comes complete with locknuts for easy installation. The NLNY25SF is annealed after final pressing to guarantee ductility and electrolytically tin plated to avoid oxidation.

Key Features:

- IP66 rated for protection against dust and water ingress.
- Self-extinguishing and halogen-free for enhanced safety.
- Straight fittings are not one-piece quick fit as the premium flexible nylon kit.
- Fittings complete with locknuts for easy installation.
- Annealed after final pressing to guarantee ductility.
- Electrolytically tin plated to avoid oxidation.

Specifications:

Surface protection: Untreated

• Halogen-free: Yes

Model: Other

Nominal Tube Diameter: 25mm

Colour: Black

ETIM Class-9.0: Coupler for conduit (EC000939)

ETIM Features:

Surface protection: Untreated (EV006034)

Halogen-free: Yes

Model: Other (EV000154)

Nominal Tube Diameter: 25mm

Colour: Black (EV000206)

Applications: The NLNY25SF is suitable for various applications where a flexible conduit gland is required, such as electrical installations, machinery, and industrial environments. It provides a secure and reliable connection for nylon conduits, ensuring protection and ease of installation.

