



MPN: NLTC35

Product Name: 35mm² Copper Tube Splice

Brand: Newlec

Category: Copper Tube Terminals

Product Description: The NLTC35 is a 35mm² copper tube splice designed for secure and efficient electrical connections. It is manufactured by Newlec, a trusted name in electrical products. This copper tube splice is specifically designed for use with copper conductors, providing a reliable and durable connection. The NLTC35 is annealed to guarantee optimum ductility, allowing for easy installation and flexibility. It is suitable for a wide range of applications and can withstand temperatures ranging from -50°C to +150°C. With a maximum voltage rating of 11kV, this copper tube splice ensures safe and efficient electrical connections.

Key Features:

- Annealed to guarantee optimum ductility.
 - Facilitated introduction of the conductor.
 - Temperature Range: -50°C to +150°C.
 - Maximum Voltage Rating: 11Kv.
 - Manufactured from electrolytic Copper tube with a purity greater than 99.9%.
 - Electrolytically tin-plated to avoid oxidization.
-

Specifications:

- Insulation: Polyvinyl chloride (PVC)
- Nominal cross section (mm²): 35 - 35
- Material: Copper
- Surface protection: Tinned

ETIM class-9.0: Solderless copper terminals for copper conductors (EC001052)

ETIM features:

- Insulation: Polyvinyl chloride (PVC) (EV000163)
- Nominal cross section (mm²): 35 - 35
- Material: Copper (EV000138)
- Surface protection: Tinned (EV001481)

Applications:

- Electrical installations
- Power distribution systems
- Industrial applications
- Residential wiring



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!