



MPN: NLRR6

Product Name: Red 0.25-1.5mm² Pre-Insulated Ring Terminal M6 Stud

Brand: Newlec

Category: Insulated Crimps

Product Description: The Red 0.25-1.5mm² Pre-Insulated Ring Terminal M6 Stud, manufactured by Newlec, is a high-quality crimping solution designed for electrical applications. This terminal is specifically designed to provide a secure and reliable connection for wires with a cross-sectional area ranging from 0.25mm² to 1.5mm². The terminal features a pre-insulated design, ensuring enhanced safety and protection against electrical shocks. With its red colour coding, it is easy to identify and differentiate from other terminals.

Key Features:

- PVC insulation for added safety and protection.
- Temperature range of -20°C to +80°C, suitable for various environments.
- Manufactured from electrolytic copper wire with a purity greater than 99.9%.
- Electrolytically tin-plated to prevent oxidization.
- Annealed to guarantee optimum ductility.
- Facilitated introduction of the conductor for easy installation.

Specifications:

• Nominal cross section (mm²): 0.25 - 0.25

Sleeve form: Short

Material: Copper

ETIM Class-9.0: Solderless copper terminals for copper conductors (EC001052)

ETIM Features:

o Bolt dimension (metric): 5

o Insulation: Polyvinyl chloride (PVC) (EV000163)

o Colour insulation: Red (EV000233)

o Nominal cross section (mm²): 0.25 - 0.25

o Sleeve form: Short (EV009889)

Material: Copper (EV000138)

Applications:

- Electrical installations
- Automotive wiring
- Industrial equipment
- DIY projects

