

Ground lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty



FEATURES & BENEFITS

A stylish, baffled ground light

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

Beam angle: 12° 34°



GL040 Ultra low-glare

2W LED ground light

FEATURES

Wattage	2W
IP rating	IP68
IK rating	IK08
Colour flexibility	Fixed colour
UGR	<10
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 65mm
Bathroom zone	1
Inrush current	N/A
Construction material	Stainless steel (316)
Weight	818g
Maximum ambient temperature	35°C
SELV	N/A
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
GL040DMBL40	4000K	34°	>80Ra	215	108	694
GL040DNBL40	4000K	12°	>80Ra	215	108	2891
GL040DMBL30	3000K	34°	>80Ra	208	104	671
GL040DNBL30	3000K	12°	>80Ra	208	104	2797
GL040DMBL27	2700K	34°	>80Ra	200	100	645
GL040DNBL27	2700K	12°	>80Ra	200	100	2689

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	3
PLR/350 1-5	N/A	Yes	No	0	1	1
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	1	1	3

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold separately	422-433
TUBE/68	Installation tube	Sold separately	236
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422