

Ground lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty



FEATURES & BENEFITS

A stylish, baffled mini ground light

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

Beam angle: 12° 30°



GL019 Ultra low-glare

1W mini LED ground light

FEATURES

Wattage	1W
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
UGR	<10
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 33mm
Bathroom zone	0
Inrush current	N/A
Construction material	Stainless steel (316)
Weight	260g
Maximum ambient temperature	50°C
SELV	N/A
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
GL019DMBL40	4000K	30°	>80Ra	68	68	125
GL019DNBL40	4000K	12°	>80Ra	78	78	2369
GL019DMBL30	3000K	30°	>80Ra	64	64	25
GL019DNBL30	3000K	12°	>80Ra	74	74	1324
GL019DMBL27	2700K	30°	>80Ra	60	60	24
GL019DNBL27	2700K	12°	>80Ra	70	70	1292

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLR/350 1-5	N/A	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	1	1	10

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold separately	422-423
TUBE332	Installation tube	Sold separately	236
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422