



GL019

1W mini LED ground light

FEATURES

Wattage	1W (350mA) 2W (700mA)
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 33mm
Bathroom zone	0
Inrush current	N/A
Construction material	Stainless steel (316)
Weight	204g
Maximum ambient temperature	50°C
SELV	N/A
Electric class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	350mA			700mA		
				lm	lm/W	lx at 1m	lm	lm/W	lx at 1m
GL019 F NW	4000K	38°	>80Ra	100	100	356	180	90	641
GL019 S NW	4000K	12°	>80Ra	100	100	1543	180	90	3087
GL019 F WW	3000K	38°	>80Ra	90	90	320	150	75	534
GL019 S WW	3000K	12°	>80Ra	90	90	1543	150	75	2572
GL019 F 27	2700K	38°	>80Ra	80	80	285	130	65	463
GL019 S 27	2700K	12°	>80Ra	80	80	1372	130	65	2229
GL019 F AMBER	Amber	38°	-	20	20	88	-	-	-
GL019 S AMBER	Amber	12°	-	20	20	407	-	-	-
GL019 F BLUE	Blue	38°	-	10	10	66	25	13	88
GL019 S BLUE	Blue	12°	-	10	10	509	25	13	407
GL019 F GREEN	Green	38°	-	80	80	352	120	60	528
GL019 S GREEN	Green	12°	-	80	80	1630	120	60	2444
GL019 F RED	Red	38°	-	35	35	154	-	-	-
GL019 S RED	Red	12°	-	35	35	712	-	-	-

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLR/350 1-5	220-240V	Yes	No	0	1	5
PLU/700 3-9	N/A	Yes	No	1	3	9

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold separately	422-423
TUBE332	Installation tube	Sold separately	236

Ground lights.

01604 495 151
collingwoodlighting.com

@collingwoodLED

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

New - can now also be used with a 700mA driver for increased light output

Compact yet powerful fitting

Shallow depth for easy installation

Robust cable for outdoor use

350mA or 700mA driver available

Beam angle: 12° 38°

