



MPN: NLBFB820

Product Name: 8mm Black 1.5mm² Pre-Insulated Crimp Bootlace Ferrule

Brand: Newlec

Category: Insulated Crimps

Product Description: The 8mm Black 1.5mm² Pre-Insulated Crimp Bootlace Ferrule is a high-quality electrical connector designed for use with flexible copper conductors. It features a polypropylene insulation for excellent electrical insulation and durability. The ferrule is annealed to guarantee optimum ductility, ensuring a secure and reliable connection. Additionally, it is electrolytically tin-plated to avoid oxidation, enhancing its longevity. The ferrule is halogen-free, making it suitable for applications where low smoke and toxicity are required. With a temperature range of -20°C to +115°C, it can withstand a wide range of operating conditions.

Key Features:

- Polypropylene insulation for excellent electrical insulation and durability.
- Annealed to guarantee optimum ductility.
- Electrolytically tin-plated to avoid oxidation.
- Halogen-free for low smoke and toxicity.
- Temperature range of -20°C to +115°C.
- Suitable for flexible copper conductors.

Specifications:

- Construction type: Standard
- Nominal cross section (mm²): 1.5
- Sleeve length (mm): 8
- Colour: Black

ETIM Class-9.0: Cable end sleeve (EC000005)

ETIM Features:

o Construction type: Standard (EV005866)

o Nominal cross section (mm²): 1.5

Sleeve length (mm): 8Colour: Black (EV000206)

o Material: Copper (EV000138)

Surface protection: Tinned (EV001481)

o Material insulation: Polypropylene (PP) (EV001608)

Applications:

- Electrical installations
- Industrial equipment
- Automotive wiring
- Control panels
- HVAC systems
- Power distribution systems

