



**MPN:** NLTBFW814

**Product Name:** White 8 x 1.4mm End Sleeve Twin Entry Insulated Bootlace Ferrule End Sleeve For 2 x 0.5mm² Diameter Cables

**Brand:** Newlec

**Category:** Insulated Crimps

---

**Product Description:** The White 8 x 1.4mm End Sleeve Twin Entry Insulated Bootlace Ferrule End Sleeve is designed for use with 2 x 0.5mm² diameter cables. It provides a secure and reliable connection for fine stranded conductors. The ferrule is made of high-quality copper, annealed to guarantee optimum ductility. It is electrolytically tin-plated to avoid oxidization and ensure long-lasting performance. The polypropylene insulation offers excellent electrical insulation properties. The ferrule is halogen-free and can withstand temperatures ranging from -20°C to +115°C.

---

#### Key Features:

- Polypropylene insulation for excellent electrical insulation properties.
  - Annealed copper for optimum ductility.
  - Electrolytically tin-plated to avoid oxidization.
  - Halogen-free for enhanced safety.
  - Temperature range: -20°C to +115°C.
  - Suitable for fine stranded conductors.
- 

#### Specifications:

- Construction type: Twin cable end sleeve
- Nominal cross section (mm²): 0.5
- Sleeve length (mm): 8
- Colour: White
- Material: Copper

---

## **ETIM Class-9.0:** Cable end sleeve (EC000005)

### **ETIM Features:**

- Construction type: Twin cable end sleeve (EV010193)
- Nominal cross section (mm<sup>2</sup>): 0.5
- Sleeve length (mm): 8
- Colour: White (EV000202)
- Material: Copper (EV000138)
- Surface protection: Tinned (EV001481)
- Material insulation: Polypropylene (PP) (EV001608)
- AWG size: 20 (EV007999)

---

### **Applications:**

- Electrical installations
- Industrial wiring
- Panel building
- Control cabinets
- Automation systems



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!