



MPN: NLBRT10

**Product Name:** Red 0.25-1.5mm 10mm Pre-Insulated Blade Terminal

**Brand:** Newlec

**Category:** Crimp Terminals

**Product Description:** The Red 10mm Pre-Insulated Blade Terminal is a high-quality crimp terminal designed for secure and reliable electrical connections. It is suitable for various applications where a strong and durable connection is required. The terminal is manufactured with precision using electrolytic copper wire with a purity greater than 99.9%. It is electrolytically tin-plated to prevent oxidization and ensure long-lasting performance. The terminal is annealed to guarantee optimum ductility, allowing for easy installation and flexibility. The PVC insulation provides excellent electrical insulation and protection against environmental factors. With a temperature range of -20°C to +80°C, this terminal is suitable for use in a wide range of operating conditions.

### **Key Features:**

- PVC insulation for excellent electrical insulation and protection.
- Temperature range of -20°C to +80°C for versatile applications.
- Manufactured from electrolytic copper wire with a purity greater than 99.9%.
- Electrolytically tin-plated to avoid oxidization.
- Annealed to guarantee optimum ductility.
- Facilitated introduction of the conductor for easy installation.

## **Specifications:**

- According to DIN: No
- Insulation: Polyvinyl chloride (PVC)
- Colour insulation: Red
- Nominal cross section (mm²): 0.25 0.25
- Sleeve form: Short

## **ETIM Class-9.0**: Solderless copper terminals for copper conductors (EC001052)

#### **ETIM Features:**

o According to DIN: No

o Insulation: Polyvinyl chloride (PVC) (EV000163)

o Colour insulation: Red (EV000233)

o Nominal cross section (mm²): 0.25 - 0.25

o Sleeve form: Short (EV009889)

o Suitable for solid cores: Yes

o Suitable for fine strand conductors: Yes

o Suitable for round conductors: Yes

o Material: Copper (EV000138)

# **Applications:**

- Electrical installations
- Automotive wiring
- Industrial equipment
- DIY projects
- And mor

