



**MPN:** NL880PS

**Product Name:** 100mm White + Automatic Shutters + Pullcord Wall/Window Fan

**Brand:** Newlec

**Category:** Domestic Fans

---

**Product Description:** The NL880PS is a 4" (100mm) intermittent extract fan designed for use in bathrooms, ensuites, and toilets. It efficiently extracts polluted air directly out of the property without the need for extra ducting. This fan can be easily wall or ceiling mounted, making it a versatile choice for various installations.

---

#### Key Features:

- Can be wall or ceiling mounted.
  - High-quality ABS mouldings.
  - CE marked and BEAB approved.
  - Automatic shutter for enhanced performance.
  - Extract rate: 24l/s.
  - Power consumption: 20W.
  - Sound level dB(A) @ 3m: 32.
- 

#### Specifications:

- Air volume, free flow (m<sup>3</sup>/h): 86.4
- Connection voltage (V): 240
- Electrical power take-up (W): 16
- Electrical connection: Terminals
- Suitable for electronic control: Yes
- Recess diameter (mm): 100
- Power consumption (W): 20
- Degree of protection (IP rating): IP44 (EV006418)

---

## **ETIM class-9.0:** Wall mounted fan (recessed mounted) (EC010930)

### **ETIM features:**

- Air volume, free flow (m³/h): 86.4
- Connection voltage (V): 240
- Electrical power take-up (W): 16
- Electrical connection: Terminals (EV020300)
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 154
- Width (mm): 154
- Recess diameter (mm): 100
- Power consumption (W): 20
- Degree of protection (IP rating): IP44 (EV006418)
- Operation: Pull cord (EV000239)
- Humidity sensor: None (EV000494)
- Louvre/shutter: With pull cord (EV022067)
- Colour: White (EV000202)

---

### **Applications:**

- Suitable for use in bathrooms, ensuites, and toilets
- Ideal for residential and commercial buildings requiring efficient air extraction



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!