



MPN: NL880TS

Product Name: 100mm White with Timer + Backdraft Shutter Standard Wall/Window Axial Fan

Brand: Newlec

Category: Domestic Fans

Product Description: The 4" (100mm) intermittent extract fan, NL880TS, is designed for use in bathrooms, ensuites, and toilets. It operates most efficiently when wall or ceiling mounted, extracting polluted air directly out of the property without the need for extra ducting.

Key Features:

- Can be wall or ceiling mounted.
- High-quality ABS mouldings.
- CE marked and BEAB approved.
- Automatic shutter.
- Extract rate: 24l/s.
- Power consumption: 20W.
- Sound level dB(A) @ 3m: 32.

Specifications:

- Air volume, free flow (m³/h): 86.4
- Connection voltage (V): 240
- Electrical power take-up (W): 16
- Electrical connection: Terminals
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 154
- Width (mm): 154
- Recess diameter (mm): 100
- Power consumption (W): 16
- Degree of protection (IP rating): IP44

ETIM class-9.0: Wall mounted fan (recessed mounted) (EC010930)

ETIM features:

- Air volume, free flow (m³/h): 86.4
- Connection voltage (V): 240
- Electrical power take-up (W): 16
- Electrical connection: Terminals (EV020300)
- Suitable for electronic control: Yes
- Suitable for transformer control: No
- Height (mm): 154
- Width (mm): 154
- Recess diameter (mm): 100
- Power consumption (W): 16
- Degree of protection (IP rating): IP44 (EV006418)
- Operation: Other (EV000154)

Applications:

Suitable for residential bathrooms, ensuites, and toilets.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!