



MPN: NLTC25

Product Name: 25mm² Copper Tube Splice

Brand: Newlec

Category: Copper Tube Terminals

Product Description: The 25mm² Copper Tube Splice is a high-quality electrical connector designed for joining copper conductors. It is manufactured by Newlec, a trusted brand in the industry. This splice is specifically designed for use with copper tubes and offers reliable and efficient electrical connections.

Key Features:

- Annealed to guarantee optimum ductility.
- Facilitated introduction of the conductor.
- Temperature Range: -50°C to +150°C.
- Maximum Voltage Rating: 11 Kv.
- Manufactured from electrolytic copper tube with a purity greater than 99.9%.
- Electrolytically tin-plated to avoid oxidization.

Specifications:

- Insulation: Polyvinyl chloride (PVC)
- Nominal cross section (mm²): 25 - 25
- Material: Copper
- Surface protection: Tinned

ETIM class-9.0: Solderless copper terminals for copper conductors (EC001052)

ETIM features:

- Insulation: Polyvinyl chloride (PVC) (EV000163)
- Nominal cross section (mm²): 25 - 25
- Material: Copper (EV000138)
- Surface protection: Tinned (EV001481)

Applications:

- Electrical installations
- Power distribution systems
- Industrial applications
- Residential wiring



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!