



MPN: NL881TN

**Product Name:** 100mm Shower Fan + Ducting Kit With Timer

**Brand:** Newlec

Category: In Line & Shower Fans

**Product Description:** Ideal for use within shower enclosures, wet areas, and en-suites, the Newlec shower fan kits are easy to install and eliminate the risks of electric shocks as the fan is situated remotely. The kit includes: fan, 1.5m flexible ducting, Internal and external grilles, screws, plugs, and cable ties.

## **Key Features:**

- Timer version adjustable: 3-20mins.
- 220-240V AC.
- Extract rate: 23.6l/s.
- Power consumption: 15W.
- Sound level: 41dB(A) @ 3m.
- Overrun timer (1-20 mins).

## **Specifications:**

- Air volume, free flow (m³/h): 84.96
- Connection voltage (V): 240
- Electrical connection: Terminals
- Recess diameter (mm): 100

# ETIM Class-9.0: Wall mounted fan (recessed mounted) (EC010930).

### **ETIM Features:**

o Air volume, free flow (m³/h): 84.96

o Connection voltage (V): 240

Electrical connection: Terminals (EV020300)

Recess diameter (mm): 100Power consumption (W): 15

Degree of protection (IP rating) IP44 (EV006418)

Operation: Other (EV000154)

Humidity sensor: None (EV000494)Louvre/shutter: None (EV000494)

o Colour: White (EV000202)

# **Applications:**

- Ideal for use in shower enclosures, wet areas, and en-suites.
- Suitable for residential and commercial applications.

