



MPN: NL798

Product Name: 2 Way Copper Disconnecting Link (6 x 50mm Copper Bar) Hard Drawn Earth Bar

Brand: Newlec

Category: Earth Bars

Product Description: The 2 Way Copper Disconnecting Link Hard Drawn Earth Bar is a high-quality solution for effective grounding and earthing applications. It features a 50mm x 6mm hard drawn copper bar, ensuring excellent conductivity and durability. The lightweight high impact PVC insulating base provides insulation and is entirely corrosion-proof. The earth bar is equipped with M10 phosphor bronze nuts, washers, and set screws for secure connections. It is available with a twin disconnecting link, offering flexibility in installation. The PVC insulating base adds an extra layer of protection.

Key Features:

- High quality 50mm x 6mm hard drawn copper bar.
 - Lightweight high impact PVC insulating base entirely corrosion proof.
 - M10 phosphor bronze nuts, washers, and set screws for secure connections.
 - Available with a twin disconnecting link.
 - PVC insulating base for added protection.
-

Specifications:

- Construction type: Surface mounting fix
- Model: Only clamp
- Height (mm): 77
- Width (mm): 90
- Length (mm): 125

ETIM Class-9.0: Equipotential bonding bar (EC001470)

ETIM Features:

- Construction type: Surface mounting fix (EV007108)
- Model: Only clamp (EV007591)
- Height (mm): 77
- Width (mm): 90
- Length (mm): 125
- Material of contact rail: Copper (EV000138)
- Material of clamp: Copper (EV000138)

Applications:

- Suitable for grounding and earthing applications in various industries.
- Ideal for use in distribution boards and electrical installations requiring reliable grounding.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!