



MPN: NL796

Product Name: 6 Way Copper With Single Disconnecting Link (6 x 50mm Copper Bar) Hard Drawn

Earth Bar

Brand: Newlec

Category: Earth Bars

Product Description: The 6 Way Copper With Single Disconnecting Link Hard Drawn Earth Bar is a high-quality solution for effective grounding and earthing applications. It features a 50mm x 6mm hard drawn copper bar, ensuring excellent conductivity and durability. The lightweight high impact PVC insulating base provides insulation and is entirely corrosion-proof. The earth bar is equipped with M10 phosphor bronze nuts, washers, and set screws for secure connections. It is available with a single disconnecting link, offering flexibility in installation. The PVC insulating base adds an extra layer of protection.

Key Features:

- High quality 50mm x 6mm hard drawn copper bar.
- Lightweight high impact PVC insulating base entirely corrosion proof.
- M10 phosphor bronze nuts, washers, and set screws for secure connections.
- Available with a single disconnecting link.
- PVC insulating base for added protection.

Specifications:

- Number of connections: 6
- Material: Copper
- Width (mm): 90
- Thickness (mm): 77

ETIM Class-9.0: Earthing rail for distribution board (EC000329)

ETIM Features:

o Number of connections: 6

o Material: Copper (EV000138)

o Width (mm): 90

o Thickness (mm): 77

o Mounting method: DIN rail (top hat rail) (EV000941)

Applications:

- Suitable for grounding and earthing applications in various industries.
- Ideal for use in distribution boards and electrical installations requiring reliable grounding.

