



**MPN: NLSTM25CSW** 

Product Name: 5.5KW 230V IP55 Metal Clad Enclosed Direct On-Line Starter With Isolator.

Brand: Newlec.

**Category:** Motor Starters

**Product Description:** The NLSTM25CSW is a Newlec starter DOL made up of a steel enclosure with stainless steel pozidrive fixing screws for its lid. This starter comes with an isolator, providing a reliable and efficient solution for motor starting applications.

# **Key Features:**

- Manufactured in accordance with EN60947-4-1.
- IP55 steel enclosure for enhanced protection against dust and water.
- Colour: RAL7035 light grey.
- Surface mounting for easy installation.
- Standard coil voltages: 230V or 400V 50/60Hz.
- Built-in start/stop and reset push button for convenient operation.
- Hand reset thermal overloads for added safety.
- Stainless steel pozidrive fixing screws for lid for durability.
- Knockouts top and bottom for flexible cable entry.

# **Specifications:**

- Kind of motor starter: Direct starter
- Rated control supply voltage at AC 50 Hz (V): 230 -
- Rated control supply voltage at AC 60 Hz (V): 230 -
- Voltage type for actuating: AC

### ETIM Class-9.0: Motor starter/Motor starter combination (EC001037)

#### **ETIM Features:**

- Kind of motor starter: Direct starter (EV004003)
- Rated control supply voltage at AC 50 Hz (V): 230 -
- Rated control supply voltage at AC 60 Hz (V): 230 -
- Voltage type for actuating: AC (EV000460)
- o Rated operation power at AC-3, 230 V, 3-phase (kW): 5.5
- o Type of electrical connection of the main circuit: Screw connection (EV000415)
- Degree of protection (IP rating): IP55 (EV006420)
- Width (mm): 184Height (mm): 184Depth (mm): 149

# **Applications:**

The NLSTM25CSW starter is suitable for various motor starting applications, including industrial machinery, pumps, fans, and more. It provides reliable and efficient performance, ensuring smooth operation of motor-driven equipment.

