



**MPN:** NLC9230

**Product Name:** 9A 230V AC Black 3 Pole 1 Normally Open AC3 Rating Contactor

**Brand:** Newlec

**Category:** Contactors

---

**Product Description:** The Newlec NLC9230 contactor is made up of 3 poles and has a 230V (50/60Hz) AC coil voltage. This contactor is designed with a full range of add-on accessories to enhance its functionality.

---

#### Key Features:

- Manufactured in accordance with EN60947-4-1.
- DIN rail mount.
- Contactors include built-in N/O auxiliary.
- Auxiliaries 10A thermal current rated 660V AC max.
- Simple and robust construction.
- High mechanical & electrical life.
- Full range of add-on accessories.
- Frame size: 1.
- Electrical connection of main circuit: Screw connection.

---

#### Specifications:

- Rated control supply voltage at AC 50 Hz (V): 230 –
- Voltage type for actuating: AC
- Rated operation current Ie at AC-1, 400 V (A): 25
- Rated operation current Ie at AC-3, 400 V (A): 9

---

## **ETIM Class-9.0:** Power contactor, AC switching (EC000066)

### **ETIM Features:**

- Rated control supply voltage at AC 50 Hz (V): 230 -
- Rated control supply voltage at AC 60 Hz (V): 230 -
- Voltage type for actuating: AC (EV000460)
- Rated operation current  $I_e$  at AC-1, 400 V (A): 25
- Rated operation current  $I_e$  at AC-3, 400 V (A): 9
- Number of auxiliary contacts as normally open contact: 1
- Type of electrical connection of main circuit: Screw connection (EV000415)

---

### **Applications:**

- This contactor is suitable for various applications that require reliable switching of electrical circuits, such as motor control, lighting control, and power distribution.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!