



MPN: NLC12230

Product Name: 12A 230V AC Black 3 Pole 1 Normally Open AC3 Rating Contactor

Brand: Newlec

Category: Contactors

Product Description: The Newlec NLC12230 contactor is made up of 3 poles and has a 230V (50/60Hz) AC coil voltage. This contactor is designed with a full range of add-on accessories to enhance its functionality.

Key Features:

- Manufactured in accordance with EN60947-4-1.
- DIN rail mount.
- Contactors include built-in N/O auxiliary.
- Auxiliaries 10A thermal current rated 660V AC max.
- Simple and robust construction.
- High mechanical & electrical life.
- Full range of add-on accessories.
- Frame size: 1.
- Electrical connection of main circuit: Screw connection.

Specifications:

- Rated control supply voltage at AC 50 Hz (V): 230 -
- Rated control supply voltage at AC 60 Hz (V): 230 -
- Voltage type for actuating: AC
- Rated operation current Ie at AC-1, 400 V (A): 25

ETIM Class-9.0: Power contactor, AC switching (EC000066)

ETIM Features:

- Rated control supply voltage at AC 50 Hz (V): 230 -
- Rated control supply voltage at AC 60 Hz (V): 230 -
- Voltage type for actuating: AC (EV000460)
- Rated operation current I_e at AC-1, 400 V (A): 25
- Rated operation current I_e at AC-3, 400 V (A): 12
- Number of auxiliary contacts as normally open contact: 1
- Type of electrical connection of main circuit: Screw connection (EV000415)

Applications:

- This contactor is suitable for various applications that require reliable switching of electrical circuits, such as motor control, lighting control, and power distribution.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!