



MPN: NLFG135

Product Name: 1 Gang 35mm Fire Rated Dry Lining Plasterboard Box

Brand: Newlec

Category: Dry Lining Boxes

Product Description A dry lining box fixes to a plasterboard wall or ceiling by sitting behind the plasterboard to give it a flush look.

Key Features

- As simple and quick to install as standard (thermoplastic) dry lining boxes.
- Fire tested up to 90 minutes with the capability of boxes being mounted back-to-back.
- Board thicknesses (65mm-15mm).
- Spring loaded lugs and brass earth terminal fitted.

Specifications:

- Material: Metal
- Material qualifier: Thermoplastic
- Degree of protection (IP rating): IP20
- Depth of device (mm): 35

ETIM Class-9.0: Cable connection plate (EC000450)

ETIM Features:

- Mounting method: Surface mounted (EV000384)
- Clamps: None (EV000494)
- Connection system: Screwed terminal (EV001008)
- Material: Metal (EV000914)
- Material qualifier: Thermoplastic (EV000403)
- Degree of protection (IP rating): IP20 (EV006405)
- Depth of device (mm): 35

Applications

- Ideal for residential and commercial electrical installations
- Suitable for use in dry lining applications for electrical fixtures and fittings
- Designed for use in fire-rated walls and ceilings



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!