



MPN: NLFG147

Product Name: 1 Gang 47mm Fire Rated Dry Lining Plasterboard Box

Brand: Newlec

Category: Dry Lining Boxes

Product Description A dry lining box fixes to a plasterboard wall or ceiling by sitting behind the plasterboard to give it a flush look.

Key Features

- As simple and quick to install as standard (thermoplastic) dry lining boxes.
 - Fire tested up to 90 minutes with the capability of boxes being mounted back-to-back.
 - Board thicknesses (65mm-15mm).
 - Spring loaded lugs and brass earth terminal fitted.
-

Specifications:

- Mounting method: Flush mounted
- Shape: Rectangular
- Construction type: Central conduit box
- Model: Single

ETIM Class-9.0: Flush mounted box/housing (EC002601)

ETIM Features:

- Mounting method: Flush mounted (EV000383)
- Shape: Rectangular (EV000220)
- Construction type: Central conduit box (EV003721)
- Model: Single (EV002646)
- Length (mm) :47
- Depth (mm): 47 - 47
- Number of entry points: 5
- Material: Other (EV000154)

Applications:

- Ideal for residential and commercial electrical installations
- Suitable for use in dry lining applications for electrical fixtures and fittings
- Designed for use in fire-rated walls and ceilings



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!