



MPN: NLSDM415C

Product Name: 15kW 400V IP55 Steel Enclosed Motor Starter With Isolator

Brand: Newlec

Category: Motor Starters

Product Description: The Newlec NLSDM415C is a star delta motor starter designed for efficient motor control. It features a robust steel enclosure with stainless steel pozidrive fixing screws for secure lid fastening. This motor starter is equipped with an isolator for added safety.

Key Features:

- Manufactured in accordance with EN60947-4-1 standards.
- IP55 steel enclosure for protection against dust and water ingress.
- Colour: RAL7035 light grey.
- Surface mounting for easy installation.
- Standard coil voltages: 230V or 400V 50/60Hz.
- Built-in start/stop and reset push button for convenient operation.
- Hand reset thermal overloads for motor protection.
- Stainless steel pozidrive fixing screws for lid.
- Knockouts provided at the top and bottom for cable entry.

Specifications:

- Voltage type for actuating: AC
- Rated operation power at AC-3, 400V (kW): 15
- Type of electrical connection of main circuit: Screw connection
- Degree of protection (IP rating): IP55

ETIM Class-9.0: Motor starter/Motor starter combination (EC001037).

ETIM Features:

- Kind of motor starter: Star-delta starter (EV004004)
- Rated control supply voltage at AC 50 Hz (V): 400-
- Rated control supply voltage at AC 60 Hz (V): 400-
- Voltage type for actuating: AC (EV000460)
- Rated operation power at AC-3, 400V (kW): 1
- Type of electrical connection of main circuit: Screw connection (EV000415).
- Degree of protection (IP rating): IP55 (EV006420)
- Width (mm): 284
- Height (mm): 184
- Depth (mm): 149

Applications:

- Suitable for controlling motors in various industrial applications.
- Ideal for use in environments where dust and water protection is required.



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!