


# JC1101/WH10

## X50

X50 Fire rated downlight 3W/5W IP65 3000/4000/5700K 400/650 lms White  
(10 pack)

### Features & Benefits

- Two wattage and three colour selectable from beneath the ceiling
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings
- Multipack of 10 with white bezel (JC1101/WH10)
- Triac dimmable as standard, see JCC.co.uk for approved dimmer list



### General Information

Mounting	Recessed
Environment	Demanding
Suitable For Zones	Zone 1
Product Group	Fire-rated Downlights
Color Finish	White
Product Shape	Round
Product Range	X50
Overall Dimensions	84Ø x 55.4 x 322 cm (see profile drawing for details)
Length (mm)	322
Height (mm)	55.4
Diameter (mm)	84
Product Weight(kg)	0.266
Light Source	LED
Light Source Features	3CCT Switchable
Additional Information	For Emergency version, use JC131003 only. Not suitable for use with JCEM002/JCEM002ST
Recommended product location	Indoor use only

Minimum Void Requirement	50mm
Method of fix	Spring clips
Distance from lighted object	0.3m
IP Rating	IP65
	Tested for use in fire-rated ceilings. Full information and upto-date fire testing certificates for ceiling system types are available on JCC.CO.UK
Duration of Fire protection ( Mins)	China
Origin of manufacturer	5 Year Warranty(Terms & conditions apply)
Warranty	Triac dimmable
Dimming Protocol Compatibility	JCC
Driver manufacturer	Downlight
Lighting Product Type 1	Fire-rated
Lighting Product Type 2	

## Electrical

Voltage Rating	230-240
Primary Running Current(Amp)	0.0018/0.0026
Operating Frequency Hz	50/60
Secondary running current(mA)	0.0083/0.0127
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage	3/5 selectable
Class	I
EMC Compliant (EN55015)	Yes
Input Electrical Connections	Live, Earth, Neutral
Dimmable	Yes, Triac dimmable only

## Thermals

Thermal Cut Out	Yes
Insulation Coverage	Loosely Cover with Mineral Wool Insulation
Minimum Void Requirement	50mm
Operating Temperature Range °C	0 to 26

## Performance Data

Energy Rating	This product contains a light source of energy efficiency class B(3W) or C (5W) for selected Wattage
Actual Lumen Output	480/700
Lumens Per Circuit Watt	160/140
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	3000/4000/5700K
Beam Angle °	60°
LOR (Light Output Ratio) %	100
Photometry Available	Yes

## Packaging

Standards & Approvals

Manufactured in accordance to

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE symbol

Certificate Of Conformity

Accredited Members

BS EN 60598:2015, 2-1, 2-2

Yes

Yes

Yes

Yes

available on request

LIA, ISO9001-2015, ISO14001-2015

