


FOXHILL

FOXHILL High Output Bulkhead - Made in Britain, IP65, LiFePO4























GENERAL DATA

Light Source	LED
Light Source Replaceable	Yes
Colour/Finish	White
Material	Polycarbonate
Diffuser Type	Prismatic
Diffuser Material	Polycarbonate
IP Rating	IP65
IK Rating	IK08
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	>200,000

DIMENSIONS & WEIGHT

Length (mm)	370	
Width (mm)	140	
Depth (mm)	90	
Weight (g)	1150	

BLE LIGHTING AND POWER LTD



ELECTRICAL

LLLC I KI C/ KL		
Input Voltage (V)	220-240	
Input Frequency (Hz)	50	
Wattage (W)	7	
Classification	Class I	
Operating Temperature (°c)	0 to +40	
Power Factor	0.95	
OPTICAL		
Colour Temperature	4000K	
CRI	80	
Beam Angle (°)	120	
Lumen Output Mains (lm)	1200	
EMERGENCY		
Battery Type	LiFePO4 2 x 3.2V	
Battery Capacity	2 × 6.8Ah	
Battery Warranty (Years)	5	
Recharge Time (hrs)	24	
Battery Replaceable	Yes	
Mode Of Operation	Maintained / Non-maintained	
Test Procedure	Manual	
Emergency Duration (Hrs)	3	
Lumen Output Emergency (lm)	930	
STANDARDS & APPROVALS		
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22	
CE Mark	Yes	
UKCA Mark	Yes	
WEEE Symbol	Yes	
Accredited Members	ISO 9001, LIA, ICEL	

BLE LIGHTING AND POWER LTD