

100mm Axial Fan with Humidistat, Pull Cord and Shutters



Download



[Operations & Maintenance Manual \(pdf\)](#)

[Web Page \(pdf\)](#)

Model: 406112

Axial extract fan with integral humidity controller, backdraught shutters and a direct switching override at low humidity. The factory setting is 75%RH at a normal 20⁰c but the humidity setting is adjustable between 60%RH to 90%RH.

Key Features

- All non pull cord variants can be ceiling mounted
- Suitable for wall or ceiling mounting
- High Quality ABS mouldings with external gloss finish
- Quiet Operation

Technical Specification

- Meets the requirements of Building Regulation Document F
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection

- Hole Diameters: Window 105mm, Wall 115mm
- Airflow: Panel Mount 88m³/hr, Window/Wall 69m³/hr

Product Range Details

- Rated Voltage 220-240v-50Hz
- Rated Wattage 16W
- Motor speed 2100rpm
- Noise Level 30dB(A)

Accessories

- Window Kit
- Wall Kit
- External wall grille
- External gravity grille
- Ducting

Dimensions

Height

-

154mm

Width

-

154mm

Depth

-

47mm

Source URL:

<http://www.anda.co.uk/products/ventilation/100mm-axial-fan-humidistat-pull-cord-and-shutters>