

Weatherproof Accessories / Powerbreaker IP66 Range

RCD Spur Weatherproof Enclosure



Technical Specification

Product Code	H92IP-X
Feature 1	Weatherproof to IP67
Feature 2	PowerBreaker technology
Feature 3	Rated trip current 30mA
Feature 4	Incorporates 13A fuse
Barcode	5012739600081
CE	Y
Colour	White with Clear Cover
Company DUNS Number	216156018
Country of Origin	China
Current (I)	10
Electrical Latching	Passive
Finish body	Gloss

Fixings supplied with product	N
Frequency (Hz) max	60
Frequency (Hz) min	50
Greenbrook Guarantee (Years)	2
HS Code	8536201090
Ingress Protection (IP)	IP67
Installation method	Surface mount
Knock-out Dimensions	6 x 20 & 4 x 25
Knock-out Qty	6 x 20 & 4 x 25
Materials Main Body	Polycarbonate
Min Order Qty	1
Operating Temperature Range max C	40
Operating Temperature Range min C	-5
Package Product Weight gross (g)	657
Product (only) Max. Depth (mm)	76
Product (only) Max. Height (mm)	125
Product (only) Max. Width (mm)	125
Product Weight net (g)	401
Rated Trip Current	30
RCD Contact Break	250
Sales Pack Qty	1
StatusCode	Active
Terminal Capacity	6
Trip Speed	20
UKCA	Y
Voltage (VAC) MAX (V)	240
Voltage (VAC) Min (V)	220
Voltage (VAC) Rated (V)	230
Wattage (W)	2300
Feature 5	High intensity LED power on indicator

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk

Feature 6

Extra fast trip action -
typically cuts the power
less than 20mS
