

Circuit Protection / Powerbreaker Portable RCD

RCD PowerBreaker In line 16A 240V



Technical Specification

|                      |                                                 |
|----------------------|-------------------------------------------------|
| Product Code         | J62-T                                           |
| Feature 1            | Suitable for BS or European power supply system |
| Feature 2            | Robust Construction                             |
| Feature 3            | Mechanical flag indicator                       |
| Feature 4            | Double Pole Breaking                            |
| Barcode              | 5012739606441                                   |
| CE                   | Y                                               |
| Colour               | Orange (Tangerine)                              |
| Company DUNS Number  | 216156018                                       |
| Country of Origin    | China                                           |
| Current (I)          | 16                                              |
| Degree of Protection | 65                                              |

|                                          |                                |
|------------------------------------------|--------------------------------|
| <b>Finish body</b>                       | Gloss                          |
| <b>Fixings supplied with product</b>     | None                           |
| <b>Frequency (Hz) max</b>                | 60                             |
| <b>Frequency (Hz) min</b>                | 50                             |
| <b>Greenbrook Guarantee (Years)</b>      | 1                              |
| <b>HS Code</b>                           | 8536201090                     |
| <b>Ingress Protection (IP)</b>           | IP65                           |
| <b>Installation method</b>               | inline                         |
| <b>Latching</b>                          | Active                         |
| <b>Materials Main Body</b>               | Polycarbonate                  |
| <b>Max Operating Current</b>             | 16                             |
| <b>Min Order Qty</b>                     | 1                              |
| <b>Operating Temperature Range max C</b> | 40                             |
| <b>Operating Temperature Range min C</b> | -5                             |
| <b>Package Product Max. Length (mm)</b>  | 180                            |
| <b>Package Product Max. Height (mm)</b>  | 85                             |
| <b>Package Product Max. Width (mm)</b>   | 102                            |
| <b>Package Product Weight gross (g)</b>  | 292                            |
| <b>Product (only) Max. Depth (mm)</b>    | 50.8                           |
| <b>Product (only) Max. Height (mm)</b>   | 161.5                          |
| <b>Product (only) Max. Width (mm)</b>    | 47                             |
| <b>Product Weight net (g)</b>            | 232                            |
| <b>RCD Contact Break</b>                 | Double pole                    |
| <b>RCD Type</b>                          | AC                             |
| <b>Sales Pack Qty</b>                    | 1                              |
| <b>StatusCode</b>                        | Active                         |
| <b>UKCA</b>                              | Y                              |
| <b>Voltage (VAC) MAX (V)</b>             | 240                            |
| <b>Voltage (VAC) Min (V)</b>             | 220                            |
| <b>Voltage (VAC) Rated (V)</b>           | 230                            |
| <b>Wattage (W)</b>                       | 3600                           |
| <b>Feature 5</b>                         | Separate test and reset button |

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

