

Timers / **Hard Wired Timers**

Timer 7 Day Mechanical Socket Box Mounted



Technical Specification

Product Code	T101A
Feature 1	Ideal for most heating applications
Feature 2	Timer ON status indicator
Feature 3	Fits 35mm dual appliance socket box should you require the timer next to a fused spur or socket outlet
Feature 4	Will fit directly to any 35mm deep socket box fitted with an earth terminal
Ambient Temperature	20
Barcode	5012739638688
Battery Back Up	N

Boost	N
CE	Y
Class Type	II
Colour	White
Company DUNS Number	216156018
Connections	Wired
Country of Origin	China
Current (I)	R=16 L=2
Display	Mechanical
Finish body	Matt
Fixings supplied with product	N
Frequency (Hz) max	50
Frequency (Hz) min	50
Greenbrook Guarantee (Years)	1
HS Code	9107000090
Ingress Protection (IP)	IP20
Installation method	Flush mount
Manual Override	Y
Materials Main Body	Polycarbonate
Maximum Load	16A for Immersion Heaters upto 3kW
Min Order Qty	1
No of Channels	1
Operating Temperature Range max C	40
Operating Temperature Range min C	-10
Package Product Weight gross (g)	159
Pollution Degree	Normal
Product (only) Max. Depth (mm)	57.4
Product (only) Max. Height (mm)	86.5
Product (only) Max. Width (mm)	86.5
Product Weight net (g)	126
Sales Pack Qty	1

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk

Settings	84 On / Off, On/Timed/Off Switch Selector
Shortest Switching Time	2 hours
StatusCode	Active
Timer Switch Type	MICRO- DISCONNECTION LIVE POLE ONLY
UKCA	Y
Voltage (VAC) MAX (V)	240
Voltage (VAC) Min (V)	220
Voltage (VAC) Rated (V)	230
Feature 5	1 Year Guarantee

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk