



VX0250PU



VX0402PU



VX0100PULED



VX0102PULED

250W Dimmer Switches

LIST NO	DESCRIPTION
VX0250PU	1 gang dimmer mains only
VX0250LV	1 gang dimmer mains/low voltage
VX0252LV	2 gang dimmer mains/low voltage

• Dimmers can be used 1 or 2 way

400W Dimmer Switches

LIST NO	DESCRIPTION
VX0400PU	1 gang dimmer mains only
VX0402PU	2 gang dimmer mains only
VX0400LV	1 gang dimmer mains/low voltage
VX0402LV	2 gang dimmer mains/low voltage

• Dimmers can be used 1 or 2 way

5-100W LED Dimmers

LIST NO	DESCRIPTION
VX0100PULED	1 gang LED dimmer
VX0102PULED	2 gang LED dimmer

Dimmer Switches 86mm x 86mm with 18.5mm plate depth

Product Standard

BS EN 60669-1
BS EN 55014

Installation Boxes

VX9409	Surface Moulded
SB655	Flush Metal



VX6677



VX6678



VX6681



VX6850



VX9215



VX0850

Pendant Sets

LIST NO	DESCRIPTION
VX6677	Pendant fitting (VX9074 & VX1/T2) 6" HR flex, T2 rating
VX6678	Pendant fitting (VX9074 & VX1/T2) 9" HR flex, T2 rating

• Heat resistant, 2 core, 0.75mm² PVC flexible cable

VX6681 Low energy 10-13W and 18W 6" Pendant set with compact Fluorescent Lampholder

• 42mm diameter Lamphshade • Accepts G24 4 pin lamp (not supplied)

VX6850 Safety Pendant 6" cord (VX9074 & VX0850)

• With heat resistant 0.75mm² cord to BS 6141 for service loads up to 2.5kg

Straight Batten Lampholders, with Terminal Block

LIST NO	DESCRIPTION
VX9215	Heat resistant, 3 terminals & earth, short skirt, T2 rating
VX9215HO	Heat resistant, 3 terminals & earth, home office skirt, T2 rating

Safety Lampholders

LIST NO	DESCRIPTION
VX0850	Safety pendant lampholder
VX0851	Safety batten lampholder

Product Standard

Pendant Set Ceiling Rose manufactured to BS67
Pendant Set Lampholders manufactured to BS5042
Straight Batten Lampholder BS EN 61184, T2 Rating
Safety Lampholder BS EN 61184 where applicable, T2 rating