


Plug Quick-Connect with Multi-Grip

- Screwless terminals
- Screwless enclosure connection, self locking
- Special gland, simultaneous cable gland and seal
- Protection degree IP44

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3			2125	2126					10	100
16	4				2129	2130				10	135
16	5				2135	2136				10	140
32	3			2137	2138					10	250
32	4				2141	2142				10	220
32	5				2147	2148				10	295



Fig.: Type 2136



2 MB 99

Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
a	53.0	60.0	66.0	74.5	74.5	74.5
b	93.5	100.5	103.0	121.0	121.0	121.5
c	134.0	141.0	142.0	174.0	174.0	174.5
d	97.5	104.5	105.5	128.0	128.0	128.5
e	18.0	18.0	18.0	23.0	23.0	23.0
f	57.5	64.5	70.5	78.0	78.0	80.0
Cond. mm² min	1	1	1	2.5	2.5	2.5
Cond. mm² max	2.5	2.5	2.5	6	6	6


Plug TE-Plus with Multi-Grip

- Screwless terminals
- High-temperature-resistant contact carrier
- Nickel plated contacts
- Special gland, simultaneous cable gland and seal
- Protection degree IP44

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3			21837	21686	21843	210169	210170	210171	10	125
16	4			21872	21839	21687	21688	21847	21849	10	145
16	5			210176	21840	21689	210178	210179	21879	10	180
32	3			21838	21690	21844	210184	210185	210186	10	240
32	4			21873	21841	21691	21692	21848	21850	10	260
32	5			210193	21842	21693	21623	210197	21885	10	310



Fig.: Type 21689



2 MB 93

Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
a	51.0	57.5	65.0	66.0	66.0	72.0
b	95.0	95.0	97.0	118.0	118.0	117.0
c	145.0	145.0	152.0	178.0	178.0	181.0
d	109.0	109.0	116.0	133.0	133.0	135.5
e	18.0	18.0	21.0	23.0	23.0	27.0
Cond. mm² min	1	1	1	2.5	2.5	2.5
Cond. mm² max	2.5	2.5	2.5	6	6	6


Plug TE with Multi-Grip

- Nickel plated contacts
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection, self locking
- Protection degree IP44

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
QUICK CONNECT®											
63	4					210761	210763			5	660
63	5					210765				5	720
Screw terminal:											
63	3			21024	2104	21025	210030	21531	21624	5	535
63	4			2149	2150	2151	2152	21300	21526	5	595
63	5			2153	2154	2155	21167	21663	21419	5	650



Fig.: Type 2155



2 MB 158

Ampere Poles	63 3	63 4	63 5
a	96.0	96.0	96.0
b	153.0	153.0	153.0
c	233.0	233.0	233.0
d	167.0	167.0	167.0
e	36.0	36.0	36.0
Cond. mm² min	6	6	6
Cond. mm² max	16	16	16