

PANEL MOUNTING SOCKET OUTLETS, angled

- IEC 60309-1/2, EN 60309, VDE 0623
- Protection degree IP44

Panel Mounting Socket Outlet


- Screw terminals
- 15° angled
- Flange 100 x 92 mm
- Kontex contact
- Box terminals
- Nickel plated contacts
- Protection degree IP44

3	4	5	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	g
2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h		
63	3			12563					10	415
63	4				12074	12565			10	430
63	5		12566	12568	12567				10	475

Products with PILOT please add "P" to the ref.no.



Fig.: Type 12567



4 MB 64

Ampere Poles	63	63	63							
a	100.0	100.0	100.0							
b	92.0	92.0	92.0							
c	85.0	85.0	85.0							
d	77.0	77.0	77.0							
e ø	6.5	6.5	6.5							
f	12.0	12.0	12.0							
h	65.0	65.0	65.0							
i	81.0	81.0	81.0							
k	80.0	80.0	80.0							
l	92.0	92.0	92.0							
Cond. mm² min	6	6	6							
Cond. mm² max	25	25	25							

Panel Mounting Socket Outlet


- Screw terminals
- 15° angled
- Flange 114 x 114 mm
- Kontex contact
- Box terminals
- Nickel plated contacts
- Protection degree IP44

3	4	5	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	g
2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h		
63	3		12134	12135	12136		12381	12230	5	420
63	4		12137	1207	1201	1204	12382	12153	5	460
63	5		12138	1208	1202	12195	12383		5	500

Products with PILOT please add "P" to the ref.no.



Fig.: Type 1202



4 MB 10

Ampere Poles	63	63	63							
a	114.0	114.0	114.0							
b	114.0	114.0	114.0							
c	90.0	90.0	90.0							
d	90.0	90.0	90.0							
e ø	6.5	6.5	6.5							
f	12.0	12.0	12.0							
h	65.0	65.0	65.0							
i	81.0	81.0	81.0							
l	92.0	92.0	92.0							
Cond. mm² min	6	6	6							
Cond. mm² max	25	25	25							


Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- 15° angled
- Flange 114 x 114 mm
- High-temperature-resistant contact carrier
- Kontex contact
- Nickel plated contacts
- Box terminals
- Protection degree IP44

3	4	5	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	g
2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h		
63	4				120321	120431			5	570
63	5				120306				5	620



Fig.: Type 120306



4 MB 266

Ampere Poles	63	63								
a	114.0	114.0								
b	114.0	114.0								
c	90.0	90.0								
d	90.0	90.0								
e ø	6.5	6.5								
f	12.0	12.0								
h	74.0	74.0								
i	81.0	81.0								
l ø	92.0	92.0								
Cond. mm² min	6	6								
Cond. mm² max	25	25								