

CLOSE END CONNECTORS NL-P SERIES for copper conductors



Description:

- Close end connectors NL-P series are particularly recommended for use with flexible conductors.
- Manufactured from electrolytic copper tube Cu-OF CW008A conform to UNI EN 13600:2003.
- Connectors are electrolytically tin plated with a minimum thickness of 3µm to avoid oxidation.
- Annealed to guarantee optimum ductility which is an absolute necessity for connectors which will have to withstand the severe deformation arising when compressed.
- The interior of the Nylon insulation sleeve is funnel shaped so as to ensure complete and easy introduction of the conductor strands.
The Nylon insulated sleeve eliminates the need to insulate the terminal by either taping or using heat shrinkable tubes.
Furthermore the Nylon sleeve avoids the possibility of conductor breakage at the barrel entrance.
- Main characteristics of the Nylon sleeves:

- DIELECTRIC STRENGTH (KV/mm)	: >16,5
- VOLUME RESISTIVITY ($\Omega \cdot \text{cm}$)	: $>10^{13}$
- MAX OPERATING TEMPERATURE (°C)	: 115-130
- FLAMMABILITY (UL-94)	: V-2
- DENSITY (g/cm ³)	: 1,14
- WATER ABSORPTION (%)	: 1,5
- BREAKING LOAD (N/mm ²)	: 77
- The close end connectors can be used within the following temperature range: - 20 ÷ + 115°C (Surge + 130° C)
- The close end connectors can be stored at a minimum temperature not below - 40°C.

Cembre SpA


Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Telefax: +39 030 3365766






www.cembre.com - E-mail: info@cembre.com

CLOSE END CONNECTORS NL-P SERIES for copper conductors

Sections and Dimensions:



Polyamide PA6.6 insulated

Cond. Size sqmm (AWG)		Ref.	Ø mm	L mm	Quantity Box/Bag
0,25÷1,5 (22÷16)		NL 03-P	9,8	21,0	1.000/100
1,5÷2,5 (16÷14)		NL 06-P	7,9	19,9	1.000/100
		NL 06-PB	6,5	13,6	1.500/100
4÷6 (12÷10)		NL 1-P	10,5	21,5	800/100
		NL 1-PG	9,0	17,8	1.000/100

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Telefax: +39 030 3365766

www.cembre.com - E-mail: info@cembre.com