

LAMP HOLDERS



5850



5851



3410



3422

Technical Specification

**Safety Pendant Lampholder (5850)**

- Wipe Clean contacts avoid lamp seizure to pins making for safe and easy lamp replacement

**Safety Batten Lampholder (5851)**

- Wipe Clean contacts avoid lamp seizure to pins making for safe and easy lamp replacement
- Batten lampholder has terminals for live, neutral, loop in and protective earth

**Standard Batten Lampholder (3410, 3420, 3422)**

- Non rising terminals
- Non stick skirt

British Standards

- Crabtree lampholders and batten lampholders are all type tested to BS EN 61184, T2 rating

Terminal Capacities

Size of cable	1.5mm <sup>2</sup>
Qty of cable	1

CEILING ROSE



5860



5861



3443

Technical Specification

- Terminals for live, neutral, loop in and protective earth

**Safety Ceiling Rose (5860)**

- Cord grip prevents strain on the terminal wiring
- Suitable for service loads up to 2.5kg

**Heavy Duty Ceiling Rose (5861)**

- Internal cord fixing give maximum load capacity 15kg

**Standard Ceiling Rose (3443)**

- Fitted with integral terminal block

British Standards

- Crabtree ceiling rose are all type tested to BS 67

Terminal Capacities

Size of cable	1.5mm <sup>2</sup>
Qty of cable	1

PENDANT SETS



5855



5856



5855/S



3450/LECFL

All Pendant sets are supplied fitted with appropriate length of heat resistant 0.75mm<sup>2</sup> twin core circular cord to BS 6141 for service loads up to 2.5kg

- 5855 comprises safety ceiling rose (5860) and safety lampholder (5850)
- 5856 comprises heavy duty ceiling rose (5861) and safety lampholder (5850)

- 5855/S comprises standard ceiling rose (3443) and safety lampholder (5850)
- 3450/LECFL comprises standard ceiling rose (3443) and low energy lampholder
- Will accept 10/13W G24q1 or 18W G24q2 4 pin plug in lamp (not supplied)