

PANEL MOUNTING SOCKET OUTLETS, straight

- With screwless Quick-Connect technology
- IEC 60309-1/2, EN 60309, VDE 0623
- Protection degree IP44

Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- Kontex contact
- Flange 75 x 75 mm
- Protection degree IP44

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3			13685	13686	13687	13688	13689	13690	10	105
16	4			13691	13692	13693	13694	13695	13696	10	120
16	5			13697	13698	132001	13699	13700	13701	10	135
32	3			13702	13703	13704	13705	13706	13707	10	165
32	4			13708	13709	13710	13711	13712	13713	10	185
32	5			13714	13715	132002	13716	13717	13718	10	220



Fig.: Type 132001

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3										
16	4										
16	5										
32	3										
32	4										
32	5										
Ampere	16	16	16								
Poles	3	4	5								
a	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0		
b	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0		
c	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0		
d	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0		
e ø	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5		
f	7.0	7.0	7.0	8.0	8.0	8.0	8.0	8.0	8.0		
h	35.5	35.5	35.5	50.0	50.0	50.0	50.0	50.0	50.0		
i	50.0	50.0	51.0	60.0	60.0	60.0	60.0	60.0	60.0		
k	74.0	84.0	91.0	94.0	94.0	94.0	94.0	94.0	102.0		
l ø	45.0	45.0	55.0	60.0	60.0	60.0	60.0	60.0	60.0		
m	8.0	12.0	16.0	17.0	17.0	17.0	17.0	17.0	22.0		
Cond. mm² min	1.5	1.5	1.5	2.5	2.5	2.5	2.5	2.5	2.5		
Cond. mm² max	4	4	4	10	10	10	10	10	10		

4 MB 263

Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- Kontex contact
- Flange 56 x 56 mm for 16A 3p, 60 x 60 mm for 16A 4p
- Protection degree IP44

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3			13656	13646	13657	13658	13659	13660	10	90
16	4			13661	13662	13663	13664	13665	13666	10	110



Fig.: Type 13663

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3										
16	4										
16	5										
32	3										
32	4										
32	5										
Ampere	16	16									
Poles	3	4									
a	56.0	60.0									
b	56.0	60.0									
c	44.0	50 - 52									
d	44.0	50 - 52									
e ø	4.4	5.5									
f	7.0	7.0									
h	35.5	35.5									
i	51.0	53.0									
k	70.0	80.0									
l ø	45.0	45.0									
m	13.0	9.0									
Cond. mm² min	1.5	1.5									
Cond. mm² max	4	4									

4 MB 101

Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- Kontex contact
- Flange 62 x 62 mm for 16A 3p, 72 x 65 mm for 16A 4p and 5p
- Protection degree IP44

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3			13667	13668	13669	13670	13671	13672	10	95
16	4			13673	13674	13675	13676	13677	13678	10	120
16	5			13679	13680	13681	13682	13683	13684	10	130



Fig.: Type 13681

											g
	2P+E Ampere	3P+E Poles	3P+N+E Poles	3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h	Qty	each
16	3										
16	4										
16	5										
32	3										
32	4										
32	5										
Ampere	16	16	16								
Poles	3	4	5								
a	62.0	72.0	72.0								
b	62.0	65.0	65.0								
c	47.0	52.0	52.0								
d	47.0	52.0	52.0								
e ø	5.5	5.5	5.5								
f	7.0	7.0	7.0								
h	35.5	35.5	35.5								
i	51.0	53.0	53.0								
k	70.0	80.0	85.0								
l ø	45.0	45.0	55.0								
m	10.0	9.0	13.0								
Cond. mm² min	1.5	1.5	1.5								
Cond. mm² max	4	4	4								

4 MB 100