

panel mounting socket outlet - straight execution, flange 55x55, fixing centers 45x45

Product description					
Order number	438				
EAN/pcs	4024941004381				
Product Group	ELV panel mounting socket outlet, straight				
Amperage	16A				
Poles	3p (3P)				
Earth 'Clock' Position	4 h				
Voltage	20 up to 25 and 40 up to 50V				
Frequency	100 up to 200Hz				
Protection	IP44				
Color code	green RAL 6002				
Connection Design	screw terminal				
Max. conductor	10,0 mm²				




Date: 28.04.2017

Further Information

Material				
Material of Enclosure	Polyamide			
Contact / Contact Carrier	tact / Contact Carrier contact carrier made of Polyamide, contacts are brass nickel plated			
Weight/pcs	0.130 kg			
Packaging unit	10 pcs			

Cee Norm UK Unit 2 Highbridge Court Stafford Park 1 Telford Shropshire TF3 3BD tel: 01952 212700 / fax: 01952 212711 / email: sales@ceenorm.co.uk

Date: 28.04.2017



Ampere	16	16	32	32	
Polzahl	2	3	2	3	
а	55,0	55,0	55,0	55,0	
b	55,0	55,0	55,0	55,0	
c	45,0	45,0	45,0	45,0	
d	45,0	45,0	45,0	45,0	
e ø	5,2	5,2	5,2	5,2	
f	6,0	6,0	6,0	6,0	
h	22,0	22,0	22,0	22,0	
i	37,0	37,0	37,0	37,0	
k	67,0	67,0	67,0	67,0	
lø	49,0	49,0	49,0	49,0	
m	12,0	12,0	12,0	12,0	
Leiter mm ² min	4	4	4	4	
Leiter mm ² max	10	10	10	10	