


Miniature Circuit Breakers

5SY and 5SP Miniature Circuit Breakers

5SP4, high-current, 10 000 A

3

Selection and ordering data

10 000		I_n	Mounting width	DT	Characteristic B	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
		A	MW ¹⁾		Article No.					kg
MCBs 10 000 A, high current										
	1P, 230/400 V AC									
	80	1.5			5SP4180-6		1	1 unit	002	0.263
	100				5SP4191-6		1	1 unit	002	0.265
	125				5SP4192-6		1	1 unit	002	0.269
	2P, 400 V AC									
	80	3			5SP4280-6		1	1 unit	002	0.532
	100				5SP4291-6		1	1 unit	002	0.527
	125				5SP4292-6		1	1 unit	002	0.534
	3P, 400 V AC									
	80	4.5			5SP4380-6		1	1 unit	002	0.800
	100				5SP4391-6		1	1 unit	002	0.787
	125				5SP4392-6		1	1 unit	002	0.793
	4P, 400 V AC									
	80	6			5SP4480-6		1	1 unit	002	1.046
	100				5SP4491-6		1	1 unit	002	1.038
	125				5SP4492-6		1	1 unit	002	1.062

10 000		I_n	Mounting width	DT	Characteristic C	Price per PU	PG	DT	Characteristic D	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
		A	MW ¹⁾		Article No.				Article No.					kg
MCBs 10 000 A, high current														
	1P, 230/400 V AC													
	80	1.5			5SP4180-7		002		5SP4180-8		1	1 unit	002	0.257
	100				5SP4191-7		002		5SP4191-8		1	1 unit	002	0.254
	125				5SP4192-7		002		--					
	2P, 400 V AC													
	80	3			5SP4280-7		002		5SP4280-8		1	1 unit	002	0.505
	100				5SP4291-7		002		5SP4291-8		1	1 unit	002	0.515
	125				5SP4292-7		002		--					
	3P, 400 V AC													
	80	4.5	▶		5SP4380-7		002		5SP4380-8		1	1 unit	002	0.762
	100		▶		5SP4391-7		002		5SP4391-8		1	1 unit	002	0.783
	125				5SP4392-7		002		--					
	4P, 400 V AC													
	80	6			5SP4480-7		002		5SP4480-8		1	1 unit	002	1.031
	100				5SP4491-7		002		5SP4491-8		1	1 unit	002	1.033
	125				5SP4492-7		002		--					

¹⁾ 1 MW (modular width) = 18 mm.