



5ST standard busbars

3

	Pin spacing MW ¹⁾	Length mm	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
5ST37 busbar system, 16 mm², 12 MW for MCBs, can be cut, with end caps									
	Single-phase, angled								
	For MCBs 1P	1	214	▶ 5ST3700		1	1 unit	020	0.039
	For MCBs 1P with AS or FC	1.5		▶ 5ST3702		1	1 unit	020	0.040
	Two-phase								
	For MCBs 2P	1		▶ 5ST3704		1	1 unit	020	0.092
	For MCBs 2P with AS or FC	1+1.5		▶ 5ST3706		1	1 unit	020	0.090
	Three-phase								
	For MCBs 3P	1		▶ 5ST3708		1	1 unit	020	0.116
	For MCBs 3P with AS or FC	1+1+1.5		▶ 5ST3711		1	1 unit	020	0.098
	For MCBs 1P with AS or FC	1.5		▶ 5ST3713		1	1 unit	020	0.098
	Four-phase								
	For MCBs 4P or 3P+N	1		▶ 5ST3715		1	1 unit	020	0.142
5ST37 busbar system, 16 mm², 56 MW for MCBs, can be cut, without end caps									
	Single-phase, angled								
	For MCBs 1P	1	1016	▶ 5ST3701		1	1 unit	020	0.196
	For MCBs 1P with AS or FC	1.5		▶ 5ST3703		1	1 unit	020	0.185
	Two-phase								
	For MCBs 2P	1		▶ 5ST3705		1	1 unit	020	0.452
	For MCBs 2P with AS or FC	1+1.5		▶ 5ST3707		1	1 unit	020	0.446
	Three-phase								
	For MCBs 3P	1		▶ 5ST3710		1	1 unit	020	0.610
	For MCBs 3P with AS or FC	1+1+1.5		▶ 5ST3712		1	1 unit	020	0.580
	For MCBs 1P with AS or FC	1.5		▶ 5ST3714		1	1 unit	020	0.540
	Four-phase								
	For MCBs 4P or 3P+N	1		▶ 5ST3716		1	1 unit	020	0.798
5ST37 busbar system, 10 mm², 56 MW, can be cut, without end caps, with touch protection									
Four-phase									
For MCBs 2P and RCBOs 1P+N	1	1008		▶ 5ST3770-2		1	10 units	020	0.400
5ST37 busbar system, 16 mm², 56 MW, can be cut, without end caps, with touch protection									
Four-phase									
For MCBs 2P and RCBOs 1P+N	1	1008		▶ 5ST3770-3		1	10 units	020	0.550
5ST37 busbar system, 10 mm², 16 MW, can be cut, without end caps, with touch protection									
Four-phase									
For RCCBs 4P, N right and 6 MCBs 1P+N	1	288		▶ 5ST3770-4		1	10 units	020	0.100
5ST37 busbar system, 16 mm², 16 MW, can be cut, without end caps, with touch protection									
Four-phase									
For RCCBs 4P, N right and 6 MCBs 1P+N	1	288		▶ 5ST3770-5		1	10 units	020	0.160
End caps for 5ST37, can be cut									
	For single-phase busbars		▶	▶ 5ST3748		1	10 units	020	0.001
	For two-phase and three-phase busbars		▶	▶ 5ST3750		1	10 units	020	0.001
	For four-phase busbars		▶	▶ 5ST3718		1	10 units	020	0.002

¹⁾ 1 MW (modular width) = 18 mm.