

PANEL MOUNTING SOCKET OUTLETS, angled

- With screwless Quick-Connect technology
- IEC 60309-1/2, EN 60309, VDE 0623
- Protection degree IP44


Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- 20° angled
- Kontex contact
- Flange 74 x 62 mm for 16A 3p,
100 x 92 mm for the other versions
- Protection degree IP44

	2P+E Ampere	3P+E Poles	3P+N+E Poles	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	g each
16	3			12771	12772	12773	12774	12775	12776	10	100
16	4			12777	12778	12779	12780	12781	12782	10	140
16	5			12783	12784	12730	12785	12786	12787	10	160
32	3			12788	12789	12790	12874	12791	12792	10	200
32	4			12793	12794	12795	12796	12797	12798	10	210
32	5			12799	12800	12801	12802	12803	12804	10	240



Fig.: Type 12730



4 MB 112

Ampere	16	16	16	32	32	32
Poles	3	4	5	3	4	5
a	74.0	100.0	100.0	100.0	100.0	100.0
b	62.0	92.0	92.0	92.0	92.0	92.0
c	60.0	85.0	85.0	85.0	85.0	85.0
d	52.0	77.0	77.0	77.0	77.0	77.0
e ø	5.5	5.5	5.5	5.5	5.5	5.5
f	8.0	8.0	8.0	8.0	8.0	8.0
h	46.0	46.0	46.0	61.0	61.0	61.0
i	48.0	50.0	55.0	68.0	68.0	60.0
k	57.0	65.0	70.0	75.0	75.0	78.0
l	52.0	65.0	70.0	75.0	75.0	78.0
α	20°	20°	20°	20°	20°	20°
Cond. mm² min	1.5	1.5	1.5	2.5	2.5	2.5
Cond. mm² max	4	4	4	10	10	10


Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- 20° angled
- Kontex contact
- Flange 110 x 110 mm
- Protection degree IP44

	2P+E Ampere	3P+E Poles	3P+N+E Poles	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	g each
16	5					12805				10	185
32	5					12806				10	260



Fig.: Type 12805



4 MB 269

Ampere	16	32				
Poles	5	5				
a	110.0	110.0				
b	110.0	110.0				
c	90.0	90.0				
d	90.0	90.0				
e ø	5.5	5.5				
f	8.0	8.0				
h	46.0	61.0				
i	56.0	60.0				
l ø	75.0	78.0				
Cond. mm² min	1.5	2.5				
Cond. mm² max	4	10				