HYDRAULIC CUTTING TOOL

general features



STORAGE								
Туре	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately				
VAL P7	727x202xh115	1,3	*	_				
		- 6						



INDUSTRIAL APPLICATION

The tool features a double speed action: a fast advancing speed for rapid approach of the blades to the cable and a slower more powerful speed for cutting.

The blades are manufactured from high strength special Steel, heat treated to ensure a long service life. The head can easily be opened to allow the cutting of running cables, and can rotate through 180 degrees, to enable the operator to work in the most comfortable position.

HT-TCO851 features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.

HYDRAULIC CUTTING HEAD



general features

Max cutting Ø mm	Max operating pressure bar	Dimensions mm		Weight
		length	width	Weight Kg
85	700	409	135	4,9

		STORAGE		
Туре	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL TC 085	465x155xh65	2,4	*	_



INDUSTRIAL APPLICATION

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 170-174)

TCO85 features the same cutting capability as HT-TCO851.