



HMC199T

MCBs 80 - 125A 15kA C Curve

Curves C

15 kA BS EN 60898-1
15 kA BS EN 60947-2

I_n 80 to 125A

Tripping Curves

"C" magnetic setting between
5 to 10 I_n .

Use

Commercial and industrial
applications.

Connection Capacity

- 35mm² flexible wire (50mm² possible with some cable pin lugs)
- 70mm² rigid wire

KEMA

Approved according to
BS EN 60898-1.



HMC299T

Single Pole MCBs 15kA C Curve

Rating	Width (26.25mm)	Cat ref.
80A	1 ½ Mod	HMC180T
100A	1 ½ Mod	HMC190T
125A	1 ½ Mod	HMC199T



HMC399T

Double Pole MCBs 15kA C Curve

Rating	Width (52.5mm)	Cat ref.
80A	3 Mod	HMC280T
100A	3 Mod	HMC290T
125A	3 Mod	HMC299T



HMC499T

Triple Pole MCBs 15kA C Curve

Rating	Width (78.75mm)	Cat ref.
80A	4 ½ Mod	HMC380T
100A	4 ½ Mod	HMC390T
125A	4 ½ Mod	HMC399T

Four Pole MCBs 15kA C Curve

Rating	Width (105mm)	Cat ref.
80A	6 Mod	HMC480T
100A	6 Mod	HMC490T
125A	6 Mod	HMC499T