



CCA141



CCA142



SP900



MD9014



CCA143



CCA144

Switch modules interchangeable with Minigrid™ modules.
We recommend the use of branded halogen lamps with all Curva® dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. These dimmer switches have not been designed for use with LED lamps. However, they may be suitable for some good quality LED lamps. For further information please contact the Click® technical support team.

MINIGRID®

Dimmer Switches

- CCA141** 1 Gang 2 Way 250Va Dimmer Switch
CCA142 2 Gang 2 Way 250Va Dimmer Switch
CCA143 3 Gang 2 Way 250Va Dimmer Switch
CCA144 4 Gang 2 Way 250Va Dimmer Switch

Dimmer Modules

- MD9010** 1-10V Analogue Dimmer Module (25 x 62mm)
MD9001 6A 2 Way Push On/Off (Non-Dimming) Module (25 x 62mm)
MD9022 250W 2 Way Dimmer Module (25 x 62mm)
MD9042 400W 2 Way Dimmer Module (25 x 62mm)
MD9014 100W Dual Mode Dimmer Module with Trim (26.5 x 55mm)
SP900 Dimmer M10 Nut Runner Tool
 Use the nut runner to easily exchange dimmer modules and create customised dimmer switch plate.

Standards: BS EN 60669-1, BS EN 55015 Type: Leading Edge, MD9014: Leading & Trailing Edge
 Back Box Depth: 25mm Minimum Cable Size: 2 x 1.5mm²
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm), 2 Gang: (146mm x 86mm x 9.5mm)

Power Socket Outlets, Fused Connection Units & Control Switches

All Curva® 13A sockets and fused connection units are tested and approved to BS1363 offering assured quality and safety. The provision of a large earth terminal on sockets and fused connection units as standard, greatly facilitates wiring and installation.

The Curva® range offers a solution for almost every possible design need and will enhance the décor of any area whether in a kitchen, bedroom, lounge or study etc...

**13A Wall Socket Outlets | Round Pin
 Wall Socket Outlets | Fused Connection Units
 Fan Isolation Switches | DP Switches**

