

Product Code: FPCH523BK

Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet With Neon



Representative Image

General Information

| | |
|----------------------------------|--|
| Dimensions | 86mm (W) x 86mm (H) x 1.3mm (D) |
| Dimensions With Gasket | 86mm (W) x 86mm (H) x 3mm (D) |
| Plate Design & Finish | Flat Plate Polished Chrome |
| Insert Colour | Black |
| Materials | Front Plate: Stainless Steel Insert & Housing: Urea Switch Cover: Stainless Steel Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel |
| Maximum Voltage | 250V~ 50Hz |
| Load Rating | 20A |
| Plate Fixing Centres | 60.3mm |
| Terminal Size | 5mmø |
| Terminal Torque | 1.8Nm |
| Terminal Capacity | 4 x 2.5mm ² |
| Double Pole | Yes |
| Twin Earth Terminals | Yes |
| Neon Indicator | Yes (Red) |
| Flex Outlet | Yes (10mmø Through Front of the Plate) |
| Ingress Protection | IP20 |
| Back Box Depth | 35mm Minimum |
| Operational Temperature | -5°C to +40°C |
| Warranty | 10 Years |

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.