

Technical Specification

CLICK® ScolmoreGROUP

Product Code: PRW034 Description: 15A Switched Round Pin Socket Outlet





General Information

Dimensions 86mm (W) x 86mm (H) x 11mm (D)

Plate Design & Finish Square Edge Polar White

Materials Front Plate & Rocker Switch: Urea

Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 15A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø

Terminal Torque 2.0Nm
Terminal Capacity 3 x 2.5mm²

Switched Yes
Single Pole Yes
Twin Earth Terminals No
Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 20 Years

Standards BS 546: 1950

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.

All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 Rev.1.4
Errors & Omissions excluded.
Specification is subject to change without notice.