

Technical Specification



Product Code: CCA052 Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional Flex

Dutlet





Representative Image

General Information

Dimensions 86mm (W) x 86mm (H) x 9.5mm (D)

Materials Front Plate, Rocker Switch & Fuse Drawer: Urea

Rear Housing: Nylon Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

Switched Yes
Double Pole Yes
Twin Earth Terminals No
Neon Indicator Yes (F

Neon Indicator Yes (Red) Fuse Fitted 13A (BS 1362)

Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C
Warranty 10 Years

Standards BS 1363-4: 2016 +A1: 2018

BS 1362:1973

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of

the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.