

Technical Specification

CLICK® ScolmoreGROUP

Product Code: FPBS066BK Description: Twin Non-Isolated Coaxial Outlet





Representative Image

General Information

 $\label{eq:decomposition} \textbf{Dimensions} \qquad \text{86mm (W)} \times \text{86mm (H)} \times \text{1.3mm (D)}$

 $\textbf{Dimensions With Gasket} \qquad \text{86mm (W) x 86mm (H) x 3mm (D)}$

Plate Design & Finish Flat Plate Brushed Stainless

Insert Colour Black

Materials Front Plate: Stainless Steel

Insert: Urea

Earth Plate: Mild Steel Terminals: Brass

Plate Fixing Centres 60.3mm

Isolated Non-isolated (Direct connection to aerial where 2 way signal is required)

Shielded No Ingress Protection IP20

Back Box Depth 16mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Additional Information Ensure

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard

wire extensions, then a non-isolated outlet is required.