



115



120 / 125



121 / 126

**Telephone Outlets**

**RJ11 Telephone Outlet**

115 Single RJ11 (Irish/US) Outlet

120 Single Telephone Outlet - Master

121 Twin Telephone Outlet - Master

125 Single Telephone Outlet - Secondary

126 Twin Telephone Outlet - Secondary

Twin outlets are 2 separate sockets and not internally linked together.

Back Box Depth: 25mm Minimum 115: 35mm Minimum Termination Type: IDC  
Dimensions: 1 Gang: (88mm x 88mm x 1.3mm\*) \*Excluding gasket

Understanding the code:  
FP - Plate Style BN - Plate Finish 411 - Product No. BK - Insert Colour.  
BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel



156



157



158



159

**Satellite Outlets (Unshielded)**

156 Non-Isolated Single Satellite Outlet

157 Isolated Satellite & Isolated Coaxial Outlet

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

**Non-Isolated Coaxial Outlets (Unshielded)**

065 Single Coaxial Outlet

066 Twin Coaxial Outlet

**Isolated Coaxial Outlets (Unshielded)**

158 Single Isolated Coaxial Outlet

159 Twin Isolated Coaxial Outlet

Back Box Depth: 25mm Minimum  
Dimensions: 1 Gang: (88mm x 88mm x 1.3mm\*) \*Excluding gasket

Understanding the code:  
FP - Plate Style BN - Plate Finish 411 - Product No. BK - Insert Colour.  
BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel